

DEVELOPMENT OF AN ERGONOMIC RISK ASSESSMENT TOOL FOR
WORK POSTURES

MOHD NASRULL BIN ABDOL RAHMAN

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Mechanical Engineering)

Faculty of Mechanical Engineering
Universiti Teknologi Malaysia

JANUARY 2014

ABSTRACT

The most widely used method for assessing work-related musculoskeletal disorders (WMSDs) is still the observational method, mainly because it is inexpensive and practical for use in a wide range of workplaces. However, there are no tools available that cover the wide range of physical risk factors at workplaces. Most of the existing observational methods have not been extensively tested for their reliability and validity during the development process. Therefore, the main objectives of this study are to (1) to develop a new observational technique called the Workplace Ergonomic Risk Assessment (WERA) method and (2) to determine the reliability and validity of the WERA method. The study was conducted in two phases: development of the WERA paper checklist from scientific evidence and literature review (Phase 1) and development of the WERA software program using Visual Basic programming (Phase 2). In the validity trials, the relationship of the main WERA body part scores to the development of pain or discomfort was statistically significant for the wrist, shoulder, and back regions. This shows that the WERA assessment provided a good indication of work related musculoskeletal disorders which may be reported as pains, aches or discomfort in the relevant body area. In the reliability trials, the results of inter-observer reliability demonstrated moderate agreement among the observers ($K=0.41$) from the feedback survey about the usability of WERA tool. On the other hand, all participants were agreed that the WERA tool was easy and quick to use, applicable to workplace assessment for the wide range of tasks, and valuable at work. The WERA tool has been developed for both paper checklist and software program use. It can be used to identify the physical risk factors associated with WMSDs at workplaces.

ABSTRAK

Kaedah yang paling banyak digunakan untuk menilai kerja yang berkaitan dengan gangguan otot berangka (WMSDs) adalah kaedah pemerhatian, ini kerana ianya adalah murah dan praktikal untuk digunakan di pelbagai tempat kerja. Walau bagaimanapun, alat yang sedia ada tidak merangkumi pelbagai faktor risiko fizikal di tempat kerja. Tambahan pula, kebanyakan kaedah pemerhatian yang sedia ada didapati tidak diuji secara meluas tentang kebolehpercayaan dan kesahihannya semasa proses pembangunan kaedah tersebut. Oleh itu, objektif utama kajian ini adalah untuk (1) untuk membangunkan satu teknik baru dalam kaedah pemerhatian yang dinamakan sebagai kaedah “*Workplace Ergonomics Risk Assessment – WERA*” (2) untuk menentukan kebolehpercayaan dan kesahihan kaedah WERA. Kajian ini telah dijalankan dalam dua fasa iaitu pembangunan kertas senarai semak WERA hasil dari bukti saintifik kajian literatur (Fasa 1) dan pembangunan program perisian WERA yang menggunakan asas pengaturcaraan visual (Fasa 2). Dalam ujian kesahihan, hubungan diantara skor WERA dengan ketidakselesaian pada bahagian utama anggota badan adalah statistik yang signifikan bagi kawasan pergelangan tangan, bahu dan belakang badan. Ia menunjukkan bahawa kaedah WERA memberikan indikasi yang baik terhadap kerja yang berkaitan dengan gangguan otot berangka yang boleh menyebabkan ketidakselesaian ataupun kesakitan anggota badan tertentu. Dalam ujian kebolehpercayaan, keputusan kebolehpercayaan antara pemerhati menunjukkan bahawa nilai persetujuan di antara pemerhati adalah sederhana ($K=0.41$) manakala hasil maklum balas daripada soal selidik mengenai kebolehgunaan kaedah WERA, semua peserta telah bersetuju bahawa kaedah WERA ini mudah dan cepat untuk digunakan serta sesuai dan bernilai untuk digunakan di pelbagai tempat kerja. Dengan membangunkan kertas senarai semak WERA dan program perisian WERA, diharapkan ianya boleh digunakan untuk mengenal pasti faktor-faktor risiko fizikal yang berkaitan dengan gangguan otot berangka di tempat kerja.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xiii
	LIST OF FIGURES	xv
	LIST OF ABBREVIATIONS	xix
	LIST OF SYMBOLS	xx
	LIST OF APPENDICES	xxi
1	INTRODUCTION	
	1.1 Overview of the Study	1
	1.2 Problem Statements	4
	1.3 Objectives of the Study	6
	1.4 Research Questions	7
	1.5 Scope of the Study	7
	1.6 Significance of the Study	8
	1.7 Organization of the Thesis	9
2	LITERATURE REVIEW	
	2.1 Introduction	11
	2.2 Ergonomic Methods for Work-related Musculoskeletal Disorders	12

2.2.1	Self-Report Questionnaires	13
2.2.2	Observational Methods	14
2.2.3	Direct Measurement Techniques	14
2.3	Observational Methods for Work-related Musculoskeletal Disorders	15
2.3.1	Ovako Working Posture Assessment System (OWAS)	16
2.3.2	Rapid Upper Limb Assessment (RULA)	17
2.3.3	Posture, Activity, Tools and Handling (PATH)	19
2.3.4	Rapid Entire Body Assessment (REBA)	21
2.3.5	Postural Loading on the Upper-Body Assessment (LUBA)	22
2.3.6	Quick Exposure Check (QEC)	24
2.3.7	Back-Exposure Sampling Tool (Back-EST)	27
2.4	Concluding Remarks	29

3 RESEARCH METHODOLOGY

3.1	Introduction	32
3.2	Development of the WERA Method	34
3.2.1	Specification of the WERA Items	34
3.2.2	Refining of the WERA Scoring System	36
3.3	Validity Trials of the WERA Method	36
3.3.1	Sample Size and Job Selection	36
3.3.2	Data Collection	39
3.3.3	Data Analysis	42
3.4	Reliability Trials of the WERA Method	44
3.4.1	Description of the Training and Observers	44
3.4.2	Data Collection	45
3.4.3	Data Analysis	47
3.5	Development of the WERA Software Program	48
3.5.1	Development of the WERA Algorithm	48
3.5.2	Design of the WERA Graphic User Interface	49
3.5.3	WERA Coding System	51

3.6	Verification of the WERA Software Program	53
3.6.1	Case Study 1: Company A	54
3.6.1.1	Sample Size and Job Selection	54
3.6.1.2	Data Collection	57
3.6.1.3	Data Analysis	59
3.6.2	Case Study 2: Company B	61
3.6.2.1	Sample Size and Job Selection	61
3.6.2.2	Data Collection	64
3.6.2.3	Data Analysis	66
3.6	Concluding Remarks	68

4 DEVELOPMENT OF THE WORKPLACE ERGONOMIC RISK ASSESSMENT (WERA) METHOD

4.1	Introduction	69
4.2	WERA Paper Checklist	69
4.2.1	Specification of the WERA Items	70
4.2.1.1	Shoulder Posture and Repetition	70
4.2.1.2	Wrist Posture and Repetition	73
4.2.1.3	Back Posture and Repetition	75
4.2.1.4	Neck Posture and Repetition	77
4.2.1.5	Leg Posture	79
4.2.1.6	Lifting the Load	81
4.2.1.7	Vibration	82
4.2.1.8	Contact Stress	83
4.2.1.9	Task Duration	84
4.2.2	Refining of the WERA Scoring System	85
4.2.2.1	WERA Scale and Scoring System	85
4.2.2.2	WERA Action Level	87
4.3	WERA Software Program	87
4.3.1	WERA User Menu	88
4.3.2	WERA Items Screenshot	89
4.3.3	WERA Final Report	96
4.7	Concluding Remarks	98

5 CASE STUDY AND RESULTS

5.1	Introduction	99
5.2	Validity Testing of WERA Method	100
5.2.1	Description of the Sample	100
5.2.2	Body Discomfort Survey	101
5.2.2.1	Wall Plastering Job	101
5.2.2.2	Bricklaying Job	102
5.2.2.3	Floor Concreting Job	102
5.2.3	WERA Assessment	103
5.2.3.1	Wall Plastering Job	103
5.2.3.2	Bricklaying Job	104
5.2.3.3	Floor Concreting Job	105
5.2.4	WERA Validation	106
5.2.4.1	Wall Plastering Job	106
5.2.4.2	Bricklaying Job	107
5.2.4.3	Floor Concreting Job	108
5.3	Reliability Testing of WERA Method	108
5.3.1	Description of the Observers	108
5.3.2	Inter-Observer Reliability	109
5.3.2.1	Task A	109
5.3.2.2	Task B	110
5.3.2.3	Task C	111
5.3.3	Percentage of Agreement	112
5.3.4	Feedback Survey from Observers	113
5.3.5	Validation of WERA Scale and Scoring System	114
5.4	Verification of WERA Software Program : Case Study 1	116
5.4.1	Description of the Sample	116
5.4.2	Body Discomfort Survey	117
5.4.2.1	Wafer Saw Job	117
5.4.2.2	Wire Bond Job	118
5.4.2.3	Multi Plunger Job	118

5.4.3	WERA Software Analysis	119
5.4.3.1	Wafer Saw Job	119
5.4.3.2	Wire Bond Job	120
5.4.3.3	Multi Plunger Job	121
5.4.4	WERA Verification	121
5.4.4.1	Wafer Saw Job	122
5.4.4.2	Wire Bond Job	122
5.4.4.3	Multi Plunger Job	123
5.5	Verification of WERA Software Program : Case Study 2	124
5.5.1	Description of the Sample	124
5.5.2	Body Discomfort Survey	125
5.5.2.1	Inspection Job	125
5.5.2.2	Transaction Job	126
5.5.2.3	Packaging Job	126
5.5.3	WERA Software Analysis	127
5.5.3.1	Inspection Job	127
5.5.3.2	Transaction Job	128
5.5.3.3	Packaging Job	129
5.5.4	WERA Verification	130
5.5.4.1	Inspection Job	130
5.5.4.2	Transaction Job	130
5.5.4.3	Packaging Job	131
5.7	Concluding Remarks	132

6 DISCUSSION

6.1	Introduction	133
6.2	Validity Testing of WERA Method	134
6.2.1	Wall Plastering Job	134
6.2.2	Bricklaying Job	136
6.2.3	Floor Concreting Job	137
6.3	Reliability Testing of WERA Method	139
6.3.1	Inter-Observer Reliability	139

6.3.2	Percentage of Agreement	140
6.3.3	Feedback Survey from Observers	141
6.3.4	Validation of WERA Scale and Scoring System	142
6.4	Verification of WERA Software Program: Case Study 1	144
6.4.1	Wafer Saw Job	144
6.4.2	Wire Bond Job	146
6.4.3	Multi Plunger Job	148
6.5	Verification of WERA Software Program: Case Study 2	150
6.5.1	Inspection Job	150
6.5.2	Transaction Job	152
6.5.3	Packaging Job	153
6.6	Concluding Remarks	155

7 CONCLUSIONS AND FUTURE WORKS

7.1	Introduction	157
7.2	Conclusions	157
7.3	Future Works	158

REFERENCES	162
-------------------	-----

Appendices A – N	176-241
------------------	---------

LIST OF TABLES

TABLE NO.	TITLE	PAGE
1.1	Risk factors assessed by different assessment methods	4
1.2	Reliability and validity studies of different assessment methods	5
2.1	Gaps of knowledge for in this research	30
2.2	Inclusion criteria for developing the WERA method	31
4.1	Combination of risk level, score and indicator	86
4.2	Combination of physical risk factors and scoring system for WERA tool	86
4.3	Risk level, final score and action level of WERA tool	87
5.1	Demographics of the workers in three jobs of construction industry (N=130)	100
5.2	WERA final score and risk level for wall plastering job	104
5.3	WERA final score and risk level for bricklaying job	105
5.4	WERA final score and risk level for floor concreting job	106
5.5	Chi-square statistical analysis (χ^2 -test) for wall plastering job	107
5.6	Chi-square statistical analysis (χ^2 -test) for bricklaying job	107
5.7	Chi-square statistical analysis (χ^2 -test) for floor concreting job	108
5.8	Demographics of observers in the training session (N=33)	109

5.9	Inter-observer reliability for Task A	110
5.10	Inter-observer reliability for Task B	111
5.11	Inter-observer reliability for Task C	112
5.12	Observers ratings on the feedback survey of WERA tool	114
5.13	WERA Inter-Item Correlations Matrix (Spearman Correlation Coefficients)	115
5.14	Demographics of the operators in three jobs of manufacturing industry (N=115)	116
5.15	WERA final score and risk level for wafer saw job	120
5.16	WERA final score and risk level for wire bond job	120
5.17	WERA final score and risk level for multi plunger job	121
5.18	Chi-square statistical analysis (χ^2 -test) for wafer saw job	122
5.19	Chi-square statistical analysis (χ^2 -test) for wire bond job	123
5.20	Chi-square statistical analysis (χ^2 -test) for multi plunger job	123
5.21	Demographics of the operators in three jobs of manufacturing industry (N=118)	124
5.22	WERA final score and risk level for inspection job	128
5.23	WERA final score and risk level for transaction job	128
5.24	WERA final score and risk level for packaging job	129
5.25	Chi-square statistical analysis (χ^2 -test) for inspection job	130
5.26	Chi-square statistical analysis (χ^2 -test) for transaction job	131
5.27	Chi-square statistical analysis (χ^2 -test) for packaging job	131

LIST OF FIGURES

FIGURES NO.	TITLE	PAGE
1.1	Occupational accidents by sector for the category of death until 2010	3
2.1	Characteristics of the different methods	12
2.2	Observational methods for assessing the WMSDs from 1977 to 2009	16
2.3	Rapid Upper Limb Assessment (RULA)	18
2.4	Posture, Activity, Tools & Handling (PATH)	20
2.5	Rapid Entire Body Assessment (REBA)	22
2.6	Postural Loading on the Upper-Body Assessment (LUBA)	23
2.7	Quick Exposure Check (QEC)	26
2.8	Back-Exposure Sampling Tool (Back-EST)	28
3.1	Development process of WERA method	33
3.2	The main WERA variables	34
3.3	The specification of the WERA items	35
3.4	Three different positions in wall plastering job: standing position (A), bending posture (B) and reaching overhead (C)	37
3.5	Two different positions for the bricklaying job, standing position (A) and bending posture (B)	38

3.6	Four different positions in floor concreting job: bending posture in left side (A), bending posture in right side (B), kneeling posture (C) and standing posture (D)	39
3.7	Research design for validity study	40
3.8	Data analysis for validity study	43
3.9	Training session of the Ergonomic and Manual Handling course	44
3.10	Research design and data collection for training session	46
3.11	WERA software algorithm	49
3.12	Design of the WERA Graphic User Interface	50
3.13	A sample of WERA code	53
3.14	Five tasks in wafer saw job: taking the wafer (T1), writing the log book (T2), cleaning the wafer (T3), inserting the wafer (T4) and operating the wafer machine (T5)	55
3.15	Four tasks in wire bond job: key in the data (T1), screen monitoring (T2), adjusting the wire (T3) and inspection the wire (T4)	56
3.16	Five tasks in multi plunger job: set up the resin tablet (T1), preparing the plunger bushes (T2), pressing the resin tablet (T3) checking the tablet loader (T4) and writing the log book (T5)	57
3.17	Research design for Case Study 1	58
3.18	Data analysis for Case Study 1	60
3.19	Five tasks in inspection job: inserting microchip roller tape (T1), rolling the microchip roller tape (T2), monitoring the microchip (T3), checking the microchip (T4) and writing the log book (T5)	62

3.20	Four tasks in transaction job: preparing microchip roller tape (T1), checking microchip roller tape (T2), key in the data (T3) and transferring microchip roller tape (T4)	63
3.21	Five tasks in packaging job: inserting microchip roller tape into cardboard (T1), packaging microchip roller tape into cardboard (T2), labelling the cardboard (T3), checking the cardboard (T4) and transferring the cardboard (T5)	64
3.22	Research design for Case Study 2	65
3.23	Data analysis for Case Study 2	67
4.1	Risk level for the shoulder posture item in the WERA tool	72
4.2	Risk level for shoulder repetition item in the WERA tool	72
4.3	Risk level for the wrist posture item of the WERA tool	74
4.4	Risk level for wrist repetition item in the WERA tool	75
4.5	Risk level for the back posture item in the WERA tool	76
4.6	Risk level for back repetition item in the WERA tool	77
4.7	Risk level for the neck posture item in the WERA tool	79
4.8	Risk level for the leg posture item in the WERA tool	80
4.9	Risk level for the lifting load item in the WERA tool	82
4.10	Risk level for vibration item in the WERA tool	83
4.11	Risk level for contact stress item in the WERA tool	84
4.12	Risk level for task duration item in the WERA tool	85
4.13	Screenshot of the WERA user menu	88
4.14	Screenshot of the WERA shoulder part	89
4.15	Screenshot of the WERA wrist part	90

4.16	Screenshot of the WERA back part	91
4.17	Screenshot of the WERA neck part	92
4.18	Screenshot of the WERA leg part	93
4.19	Screenshot of the WERA lifting load part	93
4.20	Screenshot of the WERA vibration part	94
4.21	Screenshot of the WERA contact stress part	95
4.22	Screenshot of the WERA task duration part	95
4.23	Summary table for the WERA final score and action level	96
4.24	WERA final report	97
5.1	Percentage of workers reporting to body discomfort in wall plastering job	101
5.2	Percentage of workers reporting to body discomfort in bricklaying job	102
5.3	Percentage of workers reporting to body discomfort in floor concreting job	103
5.4	The percentage of agreement from observers	113
5.5	Percentage of operators reporting to body discomfort in wafer saw job	117
5.6	Percentage of workers reporting to body discomfort in wire bond job	118
5.7	Percentage of workers reporting to body discomfort in multi plunger job	119
5.8	Percentage of workers reported to body discomfort in inspection job	125
5.9	Percentage of workers reporting to body discomfort in transaction job	125
5.10	Percentage of workers reporting to body discomfort in packaging job	127

LIST OF ABBREVIATIONS

Back-EST	-	Back Exposure Sampling Tool
BDS	-	Body Discomfort Survey
DOSH	-	Department of Occupational Safety and Health
LUBA	-	Postural Loading on the Upper-Body Assessment
MSDs	-	Musculoskeletal Disorders
NIOSH	-	National Institute of Occupational Safety and Health
OSHA	-	Occupational Safety and Health Administrative
OWAS	-	Ovako Working Posture Assessment System
PATH	-	Posture, Activity, Tools & Handling
QEC	-	Quick Exposure Check
REBA	-	Rapid Entire Body Assessment
RULA	-	Rapid Upper Limb Assessment
SHO	-	Safety and Health Officer
SPSS	-	Statistical Package for the Social Sciences
WERA	-	Workplace Ergonomic Risk Assessment
WMSDs	-	Work-related Musculoskeletal Disorders

LIST OF SYMBOLS

K	-	Cohen's Kappa Coefficient
N	-	Sample Size
SD	-	Standard Deviation
X	-	Mean
°	-	Degree
±	-	Plus-Minus
%	-	Percentage
α	-	Alpha
χ^2	-	Chi Square
p	-	Pearson Chi-Square
r	-	Spearman Correlation Coefficients

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Summary table of the observational method from 1976 to 2009	176
B	WERA Paper Checklist	179
C	Feedback Survey of WERA Tool	180
D	Self-Report Chart (Body Discomfort Survey)	181
E	WERA Coding System	182
F	WERA Assessment (Validity Study) - Wall Plastering Job	206
G	WERA Assessment (Validity Study) - Bricklaying Job	209
H	WERA Assessment (Validity Study) - Floor Concreting Job	211
I	WERA Software Program (Verification Study) - Wafer Saw Job	214
J	WERA Software Program (Verification Study) - Wire Bond Job	219
K	WERA Software Program (Verification Study) - Multi Plunger Job	223
L	WERA Software Program (Verification Study) - Inspection Job	228
M	WERA Software Program (Verification Study) - Transaction Job	233
N	WERA Software Program (Verification Study) - Packaging Job	237

CHAPTER 1

INTRODUCTION

1.1 Overview of the Study

Ergonomics is the one of main components of safety programs around the country, and many companies have begun implementing effective ergonomic programs in their workplaces (Brodie, 2008). A basic ergonomic assessment is often the starting point for a company to approach implementing such a program due to the ergonomics hazards at a workplace (Brodie, 2008; Burdorf, 2010). This approach helps the company determine whether the jobs or tasks expose employees to risk factors that could lead to musculoskeletal disorders (MSDs). By determining how the job exposes employees to ergonomic risk factors, this approach helps the company reduce the cost of occupational injuries and work-related illnesses (Li and Buckle, 1999a; Li and Buckle, 1999b; David, 2005; Brodie, 2008; Burdorf, 2010). An additional reason to invest in ergonomics at the workplace is that it helps improve the productivity of employees, which can result in increased bottom line profits of a company (Brodie, 2008; Burdorf, 2010).

Benefits from the use of ergonomics are important to industries, so an ergonomic assessment should be the first step taken in the process of safety and health assessment (Brodie, 2008; Burdorf, 2010; Takala *et al.*, 2010). The rationale for this study grew out of research needs for practical methods used to define and evaluate the ergonomics risk factors present in a job associated with work-related musculoskeletal disorders (WMSDs). It is important to identify the ergonomics stressors linked with development of WMSDs, which are key elements for any ergonomics program in developing the assessment of biomechanical exposure in workplaces (Li and Buckle, 1999a; Li and Buckle, 1999b; David, 2005; Brodie, 2008;

Burdorf, 2010). The accurate measurement of workers' exposure to the risk factors related to WMSDs are critical to both epidemiologists and ergonomists in conducting their research studies (David, 2005; Burdorf, 2010).

Work-related musculoskeletal disorders (WMSDs) are a common health problem and a major cause of disabilities (Hales and Bernard, 1996; Bernard, 1997; Kuorinka, 1998; Malchaire *et al.*, 2001). A range of physical, individual, and psychosocial risk factors are associated with the development of WMSDs. Physical risk factors are based on exposure to physical demands while performing tasks; these factors include awkward posture, forceful exertion, repetition of movement, contact stress, vibration, and task duration (Bernard, 1997; Malchaire *et al.*, 2001; Aptel *et al.*, 2002; Punnett and Wegman, 2004). Recent studies have shown that the effects of WMSDs result in productivity loss at work, sickness, absence, and disability (Bernard, 1997; Aptel *et al.*, 2002; Punnett and Wegman, 2004). According to the Department of Occupational Safety and Health (DOSH) report on occupational accidents for the category of death until August 2010 (Figure 1.1), 51% of victims were reported by the construction industry, the highest figure. The manufacturing industry was the second highest, for which 45% of victims were reported, behind the agriculture industry (26% of victims) and the transportation industry (10% of victims) (DOSH, 2010).



PT TIA
PERPUSTAKAAN TUNJUK ALAM




Figure 1.1 Occupational accidents by sector for the category of death until 2010

Musculoskeletal injuries begin with the workers experiencing discomfort or pain due to their tasks at a workplace (Hales and Bernard, 1996; Kuorinka, 1998; Malchaire *et al.*, 2001; Devereux *et al.*, 2002; Punnett and Wegman, 2004; Khan *et al.*, 2010). Due to the risk factors present at workplaces, the discomfort will lead to an increase in the severity of symptoms and will be experienced as aches and pains (Devereux *et al.*, 2002; Punnett and Wegman, 2004; Khan *et al.*, 2010). The aches and pains may eventually result in musculoskeletal injuries such as low back pain, tendonitis, or serious nerve-compression injury such as carpal tunnel syndrome (Malchaire *et al.*, 2001; Aptel *et al.*, 2002; Punnett and Wegman, 2004).

1.2 Problem Statements

Current techniques to assess the exposure of the risk factors related to WMSDs still utilize observational methods, mainly because they are inexpensive and practical for use in a wide range of workplaces whereas using the other methods would be difficult due to the disruption they would cause (Beek and Dressen, 1998; Li and Buckle, 1999a; David, 2005; Brodie, 2008; Takala *et al.*, 2010).

However, there is no tool available to covers the wide range of physical risk factors in the workplace (Table 1.1), which include posture, repetition, forceful exertion, vibration, contact stress and task duration (David, 2005; Takala *et al.*, 2010). There is a need to widen the existing range of physical risk factors and to consider the interactions among them (David, 2005). Most of the observational tools available only focus on postural assessments of various body parts rather than covering the critical physical exposure factors in the workplaces (David, 2005; Burdorf, 2010; Takala *et al.*, 2010).

Table 1.1: Risk factors assessed by different assessment methods

Method (Year of First Publication)	Risk Factors					
	Posture	Forceful Exertion	Repetition	Vibration	Contact Stress	Task Duration
Ovako Working Posture Assessment System – OWAS (1977)	×	×				
Rapid Upper Limb Assessment – RULA (1993)	×	×				
Posture, Activity, Tools & Handling – PATH (1996)	×	×		×		
Quick Exposure Check – QEC (1999)	×	×	×			×
Rapid Entire Body Assessment – REBA (2000)	×	×				
Postural Loading on the Upper Body Assessment – LUBA (2001)	×					
Back Exposure Sampling Tool – BackEst (2009)	×	×		×		

(Sources: David, 2005; Takala *et al.*, 2010)

Furthermore, most of the existing observational methods have not been extensively tested due to infrequent assessments of reliability and validity (Table 1.2) during the development process of the tools (David, 2005; Brodie, 2008; Burdorf,

2010; Takala *et al.*, 2010). The evaluation of reliability and validity are critical to the development of ergonomic exposure assessment tools, particularly for research that attempts to establish a causal relationship between ergonomic risk factors and musculoskeletal health outcomes (David, 2005; Burdorf, 2010; Takala *et al.*, 2010). Takala *et al.* (2010) stated that a major challenge in developing an observational tool is the validation of exposure assessment techniques. Poor performance of exposure assessment tools due to the lack of reliability and validity testing contributes to the scepticism regarding the work-relatedness of musculoskeletal disorders (David, 2005; Takala *et al.*, 2010).

Table 1.2: Reliability and validity studies of different assessment methods

Method (Year of First Publication)	Psychometric Properties	
	Reliability Testing	Validity Testing
Ovako Working Posture Assessment System – OWAS (1977)	×	-
Rapid Upper Limb Assessment – RULA (1993)	×	×
Posture, Activity, Tools & Handling – PATH (1996)	×	×
Quick Exposure Check – QEC (1999)	×	-
Rapid Entire Body Assessment – REBA (2000)	×	-
Postural Loading on the Upper Body Assessment – LUBA (2001)	-	×
Back Exposure Sampling Tool – BackEst (2009)	×	-

(Sources: David, 2005; Takala *et al.*, 2010)

Therefore, this research aims to develop a new type of ergonomic risk assessment tool that covers both the range of the physical risk factors associated with WMSDs and establishes the reliability and validity of the tool during the development process.

1.3 Objectives of the Study

The main objectives of this research are:

- i. To develop a new ergonomic risk assessment technique which assesses the exposure of physical risk factors associated with WMSDs.
- ii. To establish the reliability and validity of the ergonomic risk assessment tool during the development process.
- iii. To evaluate the application of the ergonomic risk assessment tool on different tasks.

The specific objectives of this research are:

- a. To develop the ergonomic risk assessment paper checklist (Phase 1) and to test its reliability and validity during the development process.
- b. To determine the validity of the ergonomic risk assessment tool that corresponds with other valid methods in the workplace. A comparative study will be performed using the Body Discomfort Survey.
- c. To investigate the inter-observer reliability of observers assessing the physical risk factors of workers performing tasks using the ergonomic risk assessment tool.
- d. To develop the ergonomic risk assessment software program (Phase 2) based on the ergonomic risk assessment paper checklist in Phase 1.
- e. To verify that the ergonomic risk assessment software program corresponds with other valid methods in the workplace. A comparative study will be performed using the Body Discomfort Survey.

1.4 Research Questions

- 1) How valid is the ergonomic risk assessment tool in the workplace? Does the ergonomic risk assessment tool correspond to the Body Discomfort Survey?
- 2) How reliable is the ergonomic risk assessment tool between users and observers? Do the users and observers have good, moderate, or low levels of agreement when assessing the physical risk factors of tasks using ergonomic risk assessment tool?
- 3) How usable is the ergonomic risk assessment tool among the users and observers? Is the ergonomic risk assessment tool easy to use, applicable to the wide range of jobs, and valuable at work?

1.5 Scope of the Study

The scope of this research encompasses the development of the observational method, which is called the Workplace Ergonomic Risk Assessment (WERA) tool. This tool covers the physical risk factors associated with work-related musculoskeletal disorders (WMSDs) at workplaces; these factors include posture, repetition, lifting the load, vibration, contact stress and task duration. This tool assessed five main body regions: shoulders, wrists, back, neck and legs. This tool did not cover the specifics of environmental factors such as noise, lighting and thermal comfort since these factors focus more on the work environment and there already exist specific tools to evaluate these factors, such as the ACGIH Threshold Limit Value for Heat Stress and Strain (2006a) for thermal comfort risk factors, the ACGIH Threshold Limit Value for Noise (2006b) for noise risk assessment and the Cornell Task Lighting Evaluation (2007) for lighting risk assessment.

During the validity test, 130 workers (Male) from the ages of 20 to 44 years have been selected to perform three jobs in the construction industry, including wall plastering, bricklaying, and floor concreting. Case Study 1 involved 115 operators (female) ranging from the ages of 20 to 35 years selected to perform three jobs at Company A located in Tangga Batu Industrial Estate, Melaka. The jobs were also in

the manufacturing industry and included wafer sawing, wire bonding, and multi-plunging. Case Study 2 involved 118 operators (Female) from the ages of 20 to 35 years selected to perform three jobs at Company B located in Senawang Industrial Estate, Negeri Sembilan. These jobs in the manufacturing industry included inspection, transaction, and packaging job. This study focused on selection of participants of the working ages of 20 to 44 because the statistical data from the Bureau of Labor Statistics (2011) reported that workers who were 20 to 44 years of age had the highest incidence rate at 134 cases per 10,000 full-time workers in the construction and manufacturing industries. Department of Occupational Safety and Health (DOSH) reported that industries with the highest occupational accidents rates included the construction and manufacturing industries (DOSH, 2010). Therefore, the validity test and case studies have been focused on the construction and manufacturing industries. This research has aided in the development of two types of the WERA tool, the WERA paper checklist and the WERA software program.

1.6 Significance of the Study

The proposed method for this study will contribute to new knowledge in the ergonomic research field, especially to knowledge of methods in ergonomic exposure assessment tools. This is because the lack of well-designed exposure assessment methods is a primary issue for epidemiological studies of work-related musculoskeletal disorders (WMSDs) (David, 2005; Burdorf, 2010; Takala *et al.*, 2010). To date, no tool has been developed to cover the range of physical risk factors related to WMSDs which carried out reliability and validity studies during the development process of the tool. This is the first ergonomic risk assessment tool that meets the research needs for practical methods to evaluate and define the ergonomics risks inherent to a job, especially factors associated with WMSDs in the workplace.

The results of this study are useful to the development of new techniques of the observational tool called the Workplace Ergonomic Risk Assessment (WERA), which covers the range of physical risk factors related to WMSDs and addresses the reliability and validity studies during the development process of the tool. Critical information may be introduced to identify the ergonomics hazards that are linked

with the development of WMSDs; it is key to examine these hazards as part of any ergonomics activity in developing the assessment of biomechanical exposure at the workplace.

In addition, assessing exposure to risk factors for WMSDs is an essential stage in the management and prevention of WMSDs, and such assessment may even form part of an overall risk assessment programme in the industry (David, 2005; Brodie, 2008; Burdorf, 2010; Takala *et al.*, 2010). Well-designed observational tools that assess the physical risk factors related to the WMSDs have been of vital importance to both epidemiologists and ergonomists in conducting research studies (David, 2005; Brodie, 2008; Burdorf, 2010; Takala *et al.*, 2010).

1.7 Organization of the Thesis

This thesis contains seven chapters. The chapters are arranged according to the sequence of objectives and the rationale of the research. The seven chapters are: Chapter 1 (Introduction), Chapter 2 (Literature Review), Chapter 3 (Research Methodology), Chapter 4 (Development of the WERA Method), Chapter 5 (Results), Chapter 6 (Discussion) and Chapter 7 (Summary, Conclusions and Future Works).

Chapter 1 describes the background of the research, the objectives to be achieved, the research scope, the significance of the research and the organization of the thesis. Chapter 2 gives an overview of the literature and primarily focuses on the discussion of the ergonomic methods used in assessing work-related musculoskeletal disorders (WMSDs). These methods are divided into three main categories: self-report questionnaires, observational methods, and direct measurement techniques. Chapter 3 explains the research methodology and focuses on the development of the WERA method, the validity of the WERA method, the reliability of the WERA method, development of the WERA software program and verification of the WERA software program in two different case studies.

Chapter 4 describes details of the development of the WERA method, which is divided into two phases: development of the WERA paper checklist (Phase 1) and development of the WERA software program (Phase 2). Chapter 5 shows the results of the validity and reliability testing of the WERA method (Phase 1) and verification

of the WERA software program (Phase 2). It is divided into six sections: introduction, validity testing of the WERA method, reliability of the WERA method, verification of the WERA software program by Case Study 1, and verification of WERA software program by Case Study 2. Chapter 6 discusses the findings from the Chapter 5, including the results of the validity and reliability testing of the WERA method (Phase 1) and verification of the WERA software program (Phase 2).

Chapter 7 concludes with the summary, further conclusions and future work on this research.



CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

The review of the literature primarily focuses on the ergonomic methods used to assess work-related musculoskeletal disorders (WMSDs). It is divided into four sections: introduction, ergonomic methods for WMSDs, observational methods for WMSDs and conclusion. Section 2.2 discusses the commonly used exposure quantification ergonomic methods for WMSDs, which include self-report questionnaires, observational methods and direct measurement techniques. To identify the gaps of knowledge in this research, Section 2.3 presents details of the observational methods that have been developed for assessing WMSDs. This section is subdivided into seven sections that discuss the types of observational tools based upon several criteria. The inclusion criteria for selecting the observational tools were as follows: (1) the year of first publication in original scientific articles from 1977 to 2009; (2) objectives of the method; (3) range of physical risk factors covered by the method; and (4) the making of the method during the development process in term of reliability and validity studies. Based on these strategies, it would be useful for the researcher to develop a proposed method based on the gaps of knowledge in Section 2.4. Designing methodology for the development process on the proposed method is outlined in Chapters 3 and 4.

2.2 Ergonomic Methods for Work-related Musculoskeletal Disorders

Lower back pain and neck pain are categorised as work-related musculoskeletal disorders (WMSDs), which are commonly experienced among workers (Hales and Bernard, 1996; Malchaire *et al.*, 2001; Punnett and Wegman, 2004). In a study by Bernard (1997), WMSDs became a serious health problem and a major cause of disabilities. WMSDs are caused by a range of physical, individual and psychological risk factors (Kuorinka, 1998; Punnett and Wegman, 2004). The physical demands include adaptation of work posture, forceful exertion, repetitive motion, vibration and task duration while performing a task (Bernard, 1997; Aptel *et al.*, 2002).

Commonly used exposure quantification ergonomic methods in work-related musculoskeletal disorder (WMSD) studies are divided into three categories: self-report questionnaires, observational methods and direct measurement techniques (Winkel and Mathiassen, 1994). Each method has its own strengths and weaknesses and may be used for different applications or purposes. Figure 2.1 illustrates some general characteristics of each method and may be used as a guide to select a method.




Figure 2.1 Characteristics of the different methods

In general, direct measurement with instrumentation results in the most specific and accurate exposure estimation, but involves significant costs. This method would be impractical for individual exposure assessment in very large populations of large-scale epidemiological studies because of the significant resources and expertise that would be required. Self-reporting using questionnaires or interview methods can be used to assess large populations but the data obtained by these methods have low validity to the level of exposure. Observational measurement methods are frequently used in field studies as a compromise between questionnaire and direct measurement methods, since the former contains strengths and weaknesses of the latter. Observational methods present the best compromise for individual exposure assessment in large-scale epidemiological studies. The following sections discuss details of the ergonomic methods, such as self-report questionnaires, observational methods and direct measurement techniques.

2.2.1 Self-Report Questionnaires

Kadefors and Forsman (2000) stated that data collection on exposure of physical risk factors in the workplace using self-reports can be obtained from workers' diaries, interviews, and questionnaires. The most recent innovations in data collection using self-report are the written record, video film self-evaluation and the web-based questionnaires (Dane *et al.*, 2002). Other information can also be collected, such as demographic variables, signs and symptoms of body parts and signs of discomfort.

The advantages of these methods are that they are easy to use, can be applied to a wide range of working situations, and are suitable for surveying a large number of subjects. To ensure that the collection of data adequately represents the group of workers that are being investigated, a large sample size is needed. Accurate interpretation of the findings requires high-cost analysis and appropriate skills. Imprecise and unreliable worker perception of exposure presents a major problem for these methods. For example, reports of having experienced neck and back pain were found to increase the probability of workers reporting higher durations and

frequencies of physical load compared to workers who were pain free in the same occupational groups (Viikari *et al.*, 1996; Balogh *et al.*, 2004).

The degree of difficulty of the self-report methods may vary depending on factors such as worker literacy, reading comprehension, or question interpretation (Spielholz *et al.*, 2001). Although the self-report methods generate doubt in quantifying the level of exposure (Pope *et al.*, 1998), other methods can be used to analyse the details of exposure risk of the occupational group (Burdorf *et al.*, 1999). The levels of reliability and validity of self-report methods are too low for use as the basis for ergonomics intervention at the workplace (Li and Buckle, 1999a).

2.2.2 Observational Methods

The most commonly used method is the observational method, which is applied to evaluate the ergonomic hazards at workplace, monitor the ergonomic improvements, and conduct research on ergonomic issues. Although this is the best method of approach, the density of the gathered data on ergonomic hazards is limited. The quantitative measurement of the exposure, risk and data can be tracked. The low cost of the assessment and its quick turnaround times are positive characteristics in the process of identifying ergonomics hazards in the workplace. A simple observational method can be used to recognize and control the ergonomic issues in the workplace. Section 2.3 discusses the details of the observational methods for work-related musculoskeletal disorders (WMSDs).

2.2.3 Direct Measurement Techniques

Attaching a sensor directly to the subject is one of the methods developed to measure the exposure variables in the workplace. Simple handheld devices and electronic goniometers can be used to obtain measurements and recordings of the range of motion while performing a task. To measure the rotation angles of fingers, wrists and forearm, a light-weight device commonly used to measure the articulating

joint of the body part directly was developed (Biometric Ltd, 1998) together with corresponding systems for computerized data analysis (Radwin and Lin, 1993). Frievalds *et al.* (2000) developed the system, which recorded the concurrent movement of wrists, hand and fingers with grip pressure and directly connected to the computer. The Lumbar Motion Monitor is one of the tools developed to record body postures and movement assessment with combination appropriate software (Marras *et al.*, 1992). It also used to record continuous data of three-dimensional components, including the trunk position, velocity and acceleration for subsequent analysis by computer (Hasson *et al.*, 2001; Bernmark and Wiktorin, 2002). Li and Buckle (1999a) found that recording the body posture with the sensor attached to the worker's body is a technique to determine the time spent in different postures during working hour. For investigating the simulation of task, the computing systems that record the three-dimensional coordinates of all body markers are more suitable. Electromyography (EMG) is another direct method that can be used to estimate muscle tension, but it requires careful interpretation due to the non-linear relationships involved (Schuldt *et al.*, 1987; Wells *et al.*, 1997). Although it may difficult to interpret, it useful in evaluating the fatigue of local muscles (Merletti and Parker, 1999). Highly accurate data can be obtained by using this method, but many practitioners assume this method is still impractical because of the time needed for analysis and for interpreting the data. To purchase the direct measurement tools, the initial investment and other resources need to be considered to accommodate the maintenance costs and the costs of highly trained and skilled staff (Li and Buckle, 1999a).

2.3 Observational Methods for Work-related Musculoskeletal Disorders

Observational methods are often used to evaluate the ergonomic risk factors in the workplace. This method is commonly applied to identify ergonomic hazards due to its simple characteristics and its low costs. Figure 2.2 shows the evolution of the observational methods in practice from 1977 to 2009. The following sections discuss the details of the observational methods related to work-related musculoskeletal disorders (WMSDs) that have been published.




Figure 2.2 Observational methods for assessing the WMSDs from 1977 to 2009

2.3.1 Ovako Working Posture Assessment System (OWAS)

The Ovako Working Posture Assessment System (OWAS) was developed to identify and evaluate poor working postures in workplaces (Karhu *et al.*, 1977). The development of the OWAS tool has been conducted in the steel industry, which was used to define the various postures in workplaces such as the one adopted while overhauling iron smelting ovens. This method uses four digit-codes to describe the whole body posture involving back, arms, legs and the weight of the load handled. The range of risk factors includes posture and forceful exertion. There were two phases that occurred during the development of OWAS. The first phase was the classification of postures and the second phase was the evaluation of the defined postures.

Over 12 work-study engineers were trained to analyse the 28 tasks in the steel plant using the OWAS tool in order to prove the reliability of the OWAS method. The results were found to be fairly good with 93% agreement between the two groups of work-study engineers (Karhu *et al.*, 1977).

In conclusion, the OWAS tool was developed to identify and evaluate poor working postures in the workplace. In addition, the concept of its reliability may need more clarification. There is no formal study that has been conducted to determine its validity during its development process.

2.3.2 Rapid Upper Limb Assessment (RULA)

A survey method known as Rapid Upper Limb Assessment (RULA) was developed to analyse upper limb disorders which were related to work tasks (McAtamney and Corlett, 1993). Part of its development involved the operators, who performed five different tasks while standing in the garment making industry and were assessed using the RULA tool. The evaluation of exposure risk factors was based on a diagram of body posture and three scoring tables were provided. In this method posture and forceful exertion risk factors are covered. Three stages were involved in the development of the RULA tool: the working posture recording, the scoring system and the scale of action levels.

Sixteen experienced operators who performed VDU-based data entry tasks were assessed using the RULA in order to establish its validity. From this experiment, body part scores showed that neck and lower arm scores were found to be statistically significant ($P < 0.01$) while trunk, upper arm, and wrist scores were not significant. More than 120 professional practitioners including physiotherapists, industrial engineers and safety and production engineers were trained to test the reliability of the RULA tool using videotape examples of operators performing screen-based keyboard operations as well as packing, sewing and brick sorting tasks. The results showed that scoring among the subjects had high consistency. There was a moderate level of agreement for inter-observer reliability and validity in the workplace (McAtamney and Corlett, 1993).

In conclusion, the RULA tool is more suitable to provide a rapid assessment of the posture, muscle functions, and forces that were applied. Figure 2.3 shows the Rapid Upper Limb Assessment (RULA).

RULA Employee Assessment Worksheet based on RULA: a survey method for the investigation of work-related upper limb disorders, McAtamney & Corlett, Applied Ergonomics 1993, 24(2), 91-99

A. Arm and Wrist Analysis

Step 1: Locate Upper Arm Position:

Step 1a: Adjust...
If shoulder is raised: +1
If upper arm is abducted: +1
If arm is supported or person is leaning: -1

Step 2: Locate Lower Arm Position:

Step 2a: Adjust...
If either arm is working across midline or out to side of body: Add +1

Step 3: Locate Wrist Position:

Step 3a: Adjust...
If wrist is bent from midline: Add +1

Step 4: Wrist Twist:

If wrist is twisted in mid-range: +1
If wrist is at or near end of range: +2

Step 5: Look-up Posture Score in Table A:
Using values from steps 1-4 above, locate score in Table A

Step 6: Add Muscle Use Score
If posture mainly static (i.e. held >10 minutes), Or if action repeated occurs 4X per minute: +1

Step 7: Add Force/Load Score
If load < 4.4 lbs (intermittent): +0
If load 4.4 to 22 lbs (intermittent): +1
If load 4.4 to 22 lbs (static or repeated): +2
If more than 22 lbs or repeated or shocks: +3

Step 8: Find Row in Table C:
Add values from steps 5-7 to obtain Wrist and Arm Score. Find row in Table C.

B. Neck, Trunk and Leg Analysis

Step 9: Locate Neck Position:

Step 9a: Adjust...
If neck is twisted: +1
If neck is side bending: +1

Step 10: Locate Trunk Position:

Step 10a: Adjust...
If trunk is twisted: +1
If trunk is side bending: +1

Step 11: Legs:
If legs and feet are supported: +1
If not: +2

Table A: Wrist Posture Score

Upper Arm	Lower Arm	Wrist Twist	Wrist Twist	Wrist Twist	Wrist Twist
1	2	3	4	5	6
1	1	1	2	2	2
2	2	2	2	2	3
3	2	3	3	3	3
4	1	2	3	3	3
5	2	3	3	3	4
6	3	3	4	4	4

Table B: Trunk Posture Score

Neck	1	2	3	4	5	6
Legs	1	2	1	2	1	2
1	1	2	3	3	4	5
2	2	3	3	4	5	5
3	3	3	3	4	5	6
4	5	5	5	6	7	7
5	7	7	7	7	8	8
6	8	8	8	8	9	9

Table C: Neck, trunk and leg score

Wrist and Arm Score	1	2	3	4	5	6	7	8
1	1	2	3	3	4	5	5	5
2	2	2	3	4	4	5	5	5
3	3	3	3	4	4	5	6	6
4	3	3	3	4	4	5	6	6
5	4	4	4	5	6	7	7	7
6	4	4	5	6	6	7	7	7
7	5	5	6	6	7	7	7	7
8	5	5	6	7	7	7	7	7

Scoring: (final score from Table C)
1 or 2 = acceptable posture
3 or 4 = further investigation, change may be needed
5 or 6 = further investigation, change soon
7 = investigate and implement change

Step 12: Look-up Posture Score in Table B:
Using values from steps 9-11 above, locate score in Table B

Step 13: Add Muscle Use Score
If posture mainly static (i.e. held >10 minutes), Or if action repeated occurs 4X per minute: +1

Step 14: Add Force/Load Score
If load < 4.4 lbs (intermittent): +0
If load 4.4 to 22 lbs (intermittent): +1
If load 4.4 to 22 lbs (static or repeated): +2
If more than 22 lbs or repeated or shocks: +3

Step 15: Find Column in Table C
Add values from steps 12-14 to obtain Neck, Trunk and Leg Score. Find Column in Table C.

Task name: _____ **Reviewer:** _____ **Date:** ____/____/____

This tool is provided without warranty. The author has provided this tool as a simple means for applying the concepts provided in RULA. © 2004 Neuse Consulting, Inc. rbanter@ergosmart.com (816) 444-1667

provided by Practical Ergonomics

Figure 2.3 Rapid Upper Limb Assessment (RULA)

2.3.3 Posture, Activity, Tools & Handling (PATH)

A work sampling-based tool known as the Posture, Activity, Tools & Handling (PATH) tool has been developed to characterized the ergonomic hazards present in highway construction work (Buchholz *et al.*, 1996). The PATH tool has been specifically developed for the construction and agriculture industries and can easily be applied to non-repetitive work.

This method used a digit-code to describe a whole body posture. The coding system was based on a modification of the Ovako Work Posture Analysing System (OWAS) coding system, which described the activity of the worker, the type of the tool used, the size or type of handles and hand grasping. These also encompass the basics of posture code of the PATH method. The range of risk factors covered includes postures and forceful exertion.

During the development process, the results of the PATH analysis were compared with simulated real time analysis in order to determine the validity of the posture codes. For recording the postures of the back and shoulders, a simulated real time analysis method has been developed. There are two sections of work collection segments in the PATH tool: the manual material handling activities and the construction activities. In addition, a simulated real time method was established to define the codes of PATH trunk postures.

Multiple training sessions have been conducted to establish the reliability of the PATH tool; these include the exercises, coding sheets and templates practice, a two-dimensional mannequin and other visual aids. The participants were first introduced to an overview of the construction taxonomy and the PATH method. Next, the participants were taught about the PATH posture codes and were asked to apply the PATH posture codes to still photographs. This task was to be completed with the 5 seconds of observation time while coding the video was performed in real time. The participants were coding the postures of workers at the construction site in real time. Inter-observer agreement has been evaluated based on the coding posture of the workers, which was performed simultaneously by the trainees and experienced observers during the real-time coding.

In conclusion, the PATH tool was developed to analyse the ergonomic risk factors and focused on posture and forceful exertion in the highway construction scenario. Figure 2.4 shows the Posture, Activity, Tools & Handling (PATH) tool.

Month / Day										Hour / Minute									
0 1 2 3 4 5 6 7 8 9										0 1 2 3 4 5 6 7 8 9									
<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>										<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>									
<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>										<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>									
<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>										<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>									
Coder	1	2	3	4	5	6	7	8											
1	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1 Lift										
2	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	2 Lower										
3	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	3 Carry										
4	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	4 Move/Place										
5	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	5 Push/pull/drag										
6	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	6 In between tasks										
7	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	7 Watch/wait/idle										
8	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	8 Not obs./not sure										
9	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	9 Walk										
10	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	10 Operate hand tool										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	11 Operate power tool										
Rec No.	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	12 Hold tool not operate										
1	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	13 Hold: steady/maintain										
2	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	14 Hold: wall/table/rail										
3	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	15 Reach										
4	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	16 Measure										
5	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	17 Mark										
6	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	18 Point/direct										
7	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	19 Climb/descend										
8	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	20 Cut with power saw										
9	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	21 Gloves on/off										
10	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	22 Guide load										
11	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	23 Handle cable/strap										
12	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	24 Pry										
13	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	25 Pull/retract wire										
14	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	26 Sort										
15	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	27 Straighten										
16	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	28 Tie rebar										
17	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	29 Tool in/out of belt										
18	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	30 Unfasten harness										
19	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	31 Bend rebar										
20	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	32 Tighten cable										
21	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	33 Read plans										
22	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	34 Reel wire										
23	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	35 Other										
24	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	36 Wire										
25	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	37 Side cutter/fogs										
26	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	38 Wire folding rule										
27	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	39 Tape measure										
28	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	40 Rebar										
29	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	41 Power saw (hand held)										
30	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	42 Table saw										
31	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	43 Harness										
32	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	44 Cable										
33	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	45 Strap										
34	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	46 Rope										
35	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	47 Radio										
36	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	48 Gloves										
37	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	49 Hook										
38	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	50 Wrench										
39	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	51 Rail										
40	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	52 Board										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	53 Torch										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	54 Plans										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	55 Spool										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	56 Marker										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	57 Ladder										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	58 Other										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	59 Hand 1: gross grasp										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	60 Hand 2: gross grasp										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	61 Hand 1: pinch										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	62 Hand 2: pinch										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	63 Hand 1: other										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	64 Hand 2: other										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	65 Hand 1: empty										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	66 Hand 2: empty										
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>											

Source from Buchholz *et al.* (1996)**Figure 2.4** Posture, Activity, Tools & Handling (PATH)

2.3.4 Rapid Entire Body Assessment (REBA)

The Rapid Entire Body Assessment (REBA) tool was developed and specifically designed for analysing the unpredictable working postures in healthcare and other service industries (Hignett and McAtamney, 2000). The evaluation of the exposure risk factors was based on the diagram of body postures and three scoring tables were provided. In this method, posture and forceful exertion risk factors are covered. Three stages were involved in the development of the REBA: the working posture recording, scoring system development and development of the scale of action levels, which provided the level of risk and further actions to be taken.

More than 14 professionals were involved in gathering and coding over 600 working postures of workers in the health care, manufacturing and electricity industries during two training sessions in order to test the reliability of the REBA tool. Refining the REBA method and starting an analysis of inter-observer reliability for the body part coding were the main objectives of this training. As a result, the inter-observer reliability was at 85% agreement. The REBA tool needs further validation, even though it was defined as a useful tool to analyse postures. This is because no formal studies have been conducted for to test the validity of this tool during the development process. Figure 2.5 shows the Rapid Entire Body Assessment (REBA).

REBA Employee Assessment Worksheet

based on Technical note: Rapid Entire Body Assessment (REBA), Hignett, McAtamney, Applied Ergonomics 31 (2000) 201-205

A. Neck, Trunk and Leg Analysis

Step 1: Locate Neck Position

Step 1a: Adjust...
If neck is twisted: +1
If neck is side bending: +1

Neck Score

Step 2: Locate Trunk Position

Step 2a: Adjust...
If trunk is twisted: +1
If trunk is side bending: +1

Trunk Score

Step 3: Legs

Adjust: 30-60° Add +1, >60° Add +2

Leg Score

Step 4: Look-up Posture Score in Table A
Using values from steps 1-3 above, locate score in Table A

Step 5: Add Force/Load Score
If load < 11 lbs: +0
If load 11 to 22 lbs: +1
If load > 22 lbs: +2
Adjust: If shock or rapid build up of force: add +1

Step 6: Score A, Find Row in Table C
Add values from steps 4 & 5 to obtain Score A. Find Row in Table C.

Scoring:
1 = negligible risk
2 or 3 = low risk, change may be needed
4 to 7 = medium risk, further investigation, change soon
8 to 10 = high risk, investigate and implement change
11+ = very high risk, implement change

B. Arm and Wrist Analysis

Step 7: Locate Upper Arm Position:

Step 7a: Adjust...
If shoulder is raised: +1
If upper arm is abducted: +1
If arm is supported or person is leaning: -1

Upper Arm Score

Step 8: Locate Lower Arm Position:

Lower Arm Score

Step 9: Locate Wrist Position:

Step 9a: Adjust...
If wrist is bent from midline or twisted: Add +1

Wrist Score

Step 10: Look-up Posture Score in Table B
Using values from steps 7-9 above, locate score in Table B

Step 11: Add Coupling Score
Well fitting Handle and mid range power grip, good: +0
Acceptable but not ideal hand hold or coupling acceptable with another body part, fair: +1
Hand hold not acceptable but possible, poor: +2
No handles, awkward, unsafe with any body part, Unacceptable: +3

Step 12: Score B, Find Column in Table C
Add values from steps 10 & 11 to obtain Score B. Find column in Table C and match with Score A in row from step 6 to obtain Table C Score.

Step 13: Activity Score
+1 1 or more body parts are held for longer than 1 minute (static)
+1 Repeated small range actions (more than 4x per minute)
+1 Action causes rapid large range changes in postures or unstable base

Task name: _____ Reviewer: _____ Date: ____/____/____

This tool is provided without warranty. The author has provided this tool as a simple means for applying the concepts provided in REBA.

© 2004 Niles Consulting, Inc. provided by Practical Ergonomics
rbarker@ergosmart.com (815) 494-1557

Figure 2.5 Rapid Entire Body Assessment (REBA)

2.3.5 Postural Loading on the Upper-Body Assessment (LUBA)

Postural Loading on the Upper-Body Assessment (LUBA) was developed as a survey method for gathering data on the discomfort ratio value of body parts corresponding to the task duration in static postures (Kee and Karwowski, 2001)

During the development process, the validity of the LUBA tool was tested by 20 male subjects who participated in the experiment. The tool measured the pain or discomfort reported. To gather the data of the subjects' discomfort in a wide range of body motions, the free modulus technique was used in the experiment. Based on the levels of angular deviations from regular joint motions, the scheme of postural classification was developed. The postures were grouped into several categories

defined by the results of the same degrees of discomfort in statistical analysis. In this study, the reference point was determined by the relationship of the lowest score of numerical discomfort to the score of discomfort for the elbow flexion. Four categories of different actions have been proposed as criteria to evaluate postural stress during work in order to enable practitioners to make the necessary corrections.

In conclusion, the LUBA tool was developed based on experimental data that analysed postural discomfort depending on the task duration in static postures. However, no formal studies have been conducted to test the reliability of this tool during the development process. Figure 2.6 shows the Postural Loading on the Upper-Body Assessment (LUBA).

Department: Analyst name:		Task:		Operator: Date:			
Joint	Motion	Class	Score	Motion	Class	Score	
Wrist	Flexion	0-20°	1	Extension	0-20°	1	
		20-60°	4		20-45°	5	
		>60°	9		>45°	11	
	Radial deviation	0-10°	1	Ulnar deviation	0-10°	1	
		10-30°	5		10-20°	5	
		>30°	10		>20°	9	
Elbow	Flexion	0-45°	1	Supination	0-90°	3	
		45-120°	3		>90°	9	
		>120°	7				
	Pronation deviation	0-70°	3				
		>70°	9				
Shoulder	Flexion	0-45°	1	Extension	0-20°	1	
		45-90°	5		20-45°	7	
		90-150°	9		45-60°	12	
		>150°	14		>60°	16	
	Adduction	0-10°	1	Abduction	0-30°	1	
		10-30°	4		30-90°	6	
		>30°	11		>90°	13	
	Medial rotation	0-30°	1	Lateral rotation	0-10°	1	
		30-90°	4		10-30°	5	
		>90°	10		>30°	10	
	Neck	Flexion	0-20°	1	Extension	0-30°	1
			20-45°	5		30-60°	9
>45°			8	>60°		15	
Lateral bending		0-30°	1	Rotation	0-30°	1	
		30-45°	5		30-60°	4	
		>45°	13		>60°	11	
Back	Flexion	0-20°	1	Extension	Not included		
		20-60°	6				
		>60°	13				
	Lateral bending	0-10°	1	Rotation	0-20°	1	
		10-20°	5		20-30°	3	
		20-30°	12		30-45°	7	
		>30°	16		>45°	14	
Postural load =							

Source from Kee and Karwowski (2001)

Figure 2.6 Postural Loading on the Upper-Body Assessment (LUBA)

2.3.6 Quick Exposure Checklist (QEC)

David *et al.* (2008) have developed an observational tool called the Quick Exposure Checklist (QEC) to evaluate the ergonomics risk factors related to work-related musculoskeletal disorders (WMSDs). Development of the QEC tool involved two phases in which a total of 206 practitioners participated in order to test, modify and validate this tool using simulated and real workplace tasks. The QEC tool assesses the four main body areas and involves practitioners and employees in the assessment.

During the development process in Phase 1, the validity of the QEC tool was tested by 18 practitioners using the QEC tool to assess four task simulations which were compared to the results of the SIMI 3D computerised motion analysis by experts. The validation was also conducted by comparing the scores of six practitioners with expert assessments using the QEC tool (Li and Buckle, 1999a; Li and Buckle, 1999b). In Phase 2, the validity test was conducted at six organisations and five tasks were assigned to each organisation. Seven practitioners with two experts from the group assessed the each job (David *et al.*, 2005).

In Phase 1, the reliability of QEC was based on comparison of the variation task score conducted by practitioners with the results of SIMI 3D computerised motion analysis by experts (Li and Buckle, 1999a; Li and Buckle, 1999b). Eighteen practitioners viewed the video recordings of 18 industrial static and dynamic activities, including the combination of repetitive and forceful characteristics in seated and standing participants. In Phase 2, the inter-observer reliability was designed to complement the trial results in Phase 1 using video film of the jobs (David *et al.*, 2005).

Training on the QEC assessment involved six practitioners who performed QEC assessment on the small range of the tasks in the workplace. The trial assessment was focused on simulated tasks to familiarize the trainees with the QEC tool and to facilitate discussion with the experts. The practitioners were observed and evaluated on the three tasks involving laboratory work using the QEC tool.

In conclusion, evaluation of the reliability and validity of the QEC tool is the most important part of the development of the QEC tool in Phase 1. The risk assessment method using video film showed that the observer-reliability of QEC had 'fair to moderate' levels of agreement. In Phase 2, the evaluation of inter-observer

REFERENCES

- Abbas, M.F., Faris, R.H., Harber, P.I., Mishriky, A.M., El- Shahaly, H.A., Waheeb, Y.H. and Kraus, J.F. (2001). Worksite and personal factors associated with carpal tunnel syndrome in an Egyptian electronics assembly factory. *Int J Occup Environ Health*. 7, 31–6
- ACGIH Threshold Limit Value for Heat Stress and Strain (2006a). Threshold limit values for chemical substances and physical agents and biological exposure indices. *American Conference of Governmental Industrial Hygienists*.
- ACGIH Threshold Limit Value for Noise (2006b). Threshold limit values for chemical substances and physical agents and biological exposure indices. *American Conference of Governmental Industrial Hygienists*.
- Aldien, Y., Welcomeb, D., Rakhejaa, S., Dongb, R. and Boileauc, P.E. (2005). Contact pressure distribution at hand-handle interface: role of hand forces and handle size. *International Journal of Industrial Ergonomics*. 35(3): 267-286.
- Altman, D. G. (1991). *Practical Statistics for Medical Research*. London: Chapman and Hall.
- Antony, N. T. and Keir, P. J. (2010). Effects of posture, movement and hand load on shoulder muscle activity. *Journal of Electromyography and Kinesiology*. 20(2): 191-198.
- Aptel, M., Aublet, C. A. and Cnockaert, J.C. (2002). Work-related musculoskeletal disorders of the upper limb. *Joint Bone Spine*. 69(6): 546-555.
- Arvidsson, I., Åkesson, I. and Hansson, G. A. (2003). Wrist movements among females in a repetitive, non-forceful work. *Applied Ergonomics* 34(4): 309-316.
- Arvidsson, I., Hansson, G.-Å., Mathiassen, S.E. and Skerfving, S. (2008). Neck postures in air traffic controllers with and without neck/shoulder disorders. *Applied Ergonomics*. 39(2): 255-260.
- Bakker, E. W., Verhagen, A. P., Van, T. E., Lucas, C. and Koes, B.W. (2009). Spinal mechanical load as a risk factor for low back pain: a systematic review of prospective cohort studies. *Spine (Phila Pa 1976)*. 34:E281-E293.

- Balogh, I., Ørbæk, P., Ohlsson, K., Nordander, C., Unge, J. and Winkel, J. (2004). Self-assessed and directly measured occupational physical activities—influence of musculoskeletal complaints, age and gender. *Appl Ergon.* 35:49–56.
- Beek, V. D. and Dressen, F. (1998). Assessment of mechanical exposure in ergonomic epidemiology. *Occup Environ Med.* 55: 291–299.
- Bernard, B. P. (1997). *Musculoskeletal disorders and workplace factors. A critical review of epidemiologic evidence for work-related musculoskeletal disorders of the neck, upper extremity, and low back.* National Institute for Occupational Safety and Health (NIOSH). Cincinnati, OH.
- Boschman, J.S., Molen, V. D. H.F., Sluiter, J. K. and Frings-Dresen, M. H. (2011). Occupational demands and health effects for bricklayers and construction supervisors: A systematic review. *Am J Ind Med.* 54, 55-77.
- Brodie, D. M. (2008). Ergonomics Risk Assessment: Determining When, Why, Who and How You Should Perform One (On-line). *Occupational Hazard – Web E-Blast.* (Accessed 8.7.2010).
- Beach, T. A. C., Coke, S. K. and Callaghan, J. P. (2006). Upper body kinematic and low-back kinetic responses to precision placement challenges and cognitive distractions during repetitive lifting. *International Journal of Industrial Ergonomics.* 36(7): 637-650.
- Bernmark, E. and Wiktorin, C. (2002). A triaxial accelerometer for measuring arm movements. *Appl Ergon.* 33:541–547.
- Besa, A. J., Valero, F. J., Suñer, J. L. and Carballeira J. (2007). Characterisation of the mechanical impedance of the human hand-arm system: The influence of vibration direction, hand-arm posture and muscle tension. *International Journal of Industrial Ergonomics* 37(3): 225-231.
- Bin, W. S., Richardson, S. and Yeow, P.H. (2010). An ergonomics study of a semiconductors factory in an IDC for improvement in occupational health and safety. *Int J Occup Saf Ergon.* 16(3),345-56.
- Biometrics Ltd. (1998). *Goniometer and Torsiometer Operating Manual.* Biometrics Ltd, 1998; 1–24.
- Brookham, R. L., Wong, J. M. and Dickerson, C. R.(2010). Upper limb posture and submaximal hand tasks influence shoulder muscle activity. *International Journal of Industrial Ergonomics.* 40(3): 337-344.

- Buchholz, B., Paquet, V., Punnett, L., Lee, D. and Moir S. (1996). PATH: A work sampling-based approach to ergonomic job analysis for construction and other non-repetitive work. *Applied Ergonomic*. 27(3): 177-187.
- Burdorf, A. (1999). Editorial; In musculoskeletal epidemiology are we asking the unanswerable in questionnaires on physical load? *Scand J Work Environ Health*. 25:81–83.
- Burdorf, A. (2010). The role of assessment of biomechanical exposure at the workplace in the prevention of musculoskeletal disorders. *Scand J Work Environ Health*. 36(1): 1-2.
- Bureau of Labor Statistics (2011). *Incidence rates of nonfatal occupational injuries and illnesses by major industry sector*. U.S. Department of Labor.
- Burgess, R., Plooy, A., Fraser, K. and Ankrum, D.R. (1999). The influence of computer monitor height on head and neck posture. *International Journal of Industrial Ergonomics*. 23(3): 171-179.
- Burström, L. and Sörensson, A. (1999). The influence of shock-type vibrations on the absorption of mechanical energy in the hand and arm. *International Journal of Industrial Ergonomics* 23(5-6): 585-594.
- Busche, K. (2008). Neurologic Disorders Associated with Weight lifting and Bodybuilding. *Neurologic Clinics* 26(1): 309-324.
- Bulthuis, B.M., Begemann, M.J.T., Binkhorst, R.A., Vink, P., Daanen, H.A.M. and Ligteringen, J. (1991). Work load in the building industry. On-site data capture of biomechanical and physiological load of gypsum bricklayers. In: Queinnec, Y. and Daniellou, F. (Eds.) *Designing for Everyone: Proceedings of the 11th Congress of the International Ergonomics Association*. Paris (London: Taylor and Francis) : Volume 1, pp. 275-277.
- Carey, E. J. and Gallwey, T. J. (2002). Effects of wrist posture, pace and exertion on discomfort. *International Journal of Industrial Ergonomics*. 29(2): 85-94.
- Chaffin, D. B., Andersson, G. B. J. and Martin, B. J. (2006). *Occupational Biomechanics*. (4th ed.). New York : John Wiley & Sons, Inc.
- Chee, H.L. and Rampal, K.G., (2004a). Ergonomic Risk Factors of Work Processes in the Semiconductor Industry in Peninsular Malaysia. *Industrial Health*. 42, 373–381.

- Chee, H.L. and Rampal, K.G., (2004b). Work-related musculoskeletal problems among women workers in the semiconductor industry in peninsular Malaysia. *International Journal of Occupational and Environmental Health*. 10, 63-71.
- Chen, F. F., Lo, S. F., Meng, N. H., Lin, C. L. and Chou L. W. (2006). Effects of wrist position and contraction on wrist flexors H-reflex, and its functional implications. *Journal of Electromyography and Kinesiology*. 16(5), 440-447.
- Cherng, J. G., Eksioglu, M. and Kizilaslan K. (2009). Vibration reduction of pneumatic percussive rivet tools: Mechanical and ergonomic re-design approaches. *Applied Ergonomics*. 40(2), 256-266.
- Chiou, S.S., Pan, C.S. and Keane, P. (2000). Traumatic injury among drywall installers, 1992 to 1995. *Journal of Occupational and Environmental Medicine*. 42 (11), 1101-1108.
- Ciriello, V.M., Snook, S.H., Webster, B.S. and Dempsey, P. (2001). Psychophysical study of six hand movements. *Ergonomics*. 44: 922-936.
- Cohen, J., (1988). *Statistical power analysis for the behavioral sciences*. Second Edition. Lawrence Erlbaum Associated, Hillsdale, NJ.
- Corlett, E. N. and Bishop, R. P. (1976). A technique for assessing postural discomfort. *Ergonomics*. 19(2): 175-182.
- Cornell Task Lighting Evaluation (2007). *Research & Tools Kit for Workplace Assessment Tool*. Cornell University, USA
- Côté, J. N., Raymond, D., Mathieu, P. A., Feldman, A. G. and Levin MF. (2005). Differences in multi-joint kinematic patterns of repetitive hammering in healthy, fatigued and shoulder-injured individuals. *Clinical Biomechanics*. 20(6): 581-590.
- Dane, D., Feuerstein, M., Huang, G., Dimberg, L., Ali, D. and Lincoln, A. (2002). Measurement properties of a self-report index of ergonomic exposures for use in an office environment. *J Occup Environ Med*. 44:73-81.
- David, G. C. (2005). Ergonomic methods for assessing exposure to risk factors for work-related musculoskeletal disorders. *Occupational Medicine* 55: 190-199.
- David, G., Woods V. and Buckle, P. (2005). *Further Development of the Usability and Validity of the Quick Exposure Check*. University of Surrey, Guildford: Health and Safety Executive.

- David, G., Woods, V., Li, G. and Buckle, P. (2008). The development of the Quick Exposure Check (QEC) for assessing exposure to risk factors for work-related musculoskeletal disorders. *Applied Ergonomics*. 39: 57-69.
- Diederichsen, L. P., J. Nørregaard, Dyhre-Poulsen, P., Winther, A., Tufekovic, G., Bandholm, T., Rasmussen, L.R. and Krogsgaard, M. (2007). The effect of handedness on electromyographic activity of human shoulder muscles during movement. *Journal of Electromyography and Kinesiology*. 17(4): 410-419.
- Devereux, J. J., Vlachonikolis, I. G. and Buckle, P. W. (2002). Epidemiological study to investigate potential interaction between physical and psychosocial factors at work that may increase the risk of symptoms of musculoskeletal disorder to the neck and upper limb. *Occup. Environ. Med.* 59: 269-277.
- Dennis, G. J. and Barrett, R. S. (2003). Spinal loads during two-person team lifting: effect of load mass distribution. *International Journal of Industrial Ergonomics*. 32(5): 349-358.
- Dolan, P. and Adams, M. A. (1998). Repetitive lifting tasks fatigue the back muscles and increase the bending moment acting on the lumbar spine. *Journal of Biomechanics*. 31(8): 713-721.
- Dong, R. G., McDowell, T. W., Welcome, D.E., Smutz, W.P. , Schopper, A.W., Warren, C., Wu, J.Z. and Rakheja, S. (2003). On-the-hand measurement methods for assessing effectiveness of anti-vibration gloves. *International Journal of Industrial Ergonomics*. 32(4): 283-298.
- Department of Occupational Safety and Health (DOSH) (2010). *Statistic Report of Occupational Accidents for the Category of Death until August 2010*. Malaysia: DOSH
- Department of Occupational Safety and Health (DOSH) (2002). *Guideline on Occupational Safety and Health for Standing at Work*. Malaysia: DOSH
- Department of Occupational Safety and Health (DOSH) (2003), *Guideline on Occupational Safety and Health for Seating at Work*. Malaysia: DOSH
- Duclos, C., Roll, R., Kavounoudias, A., Mongeau, J. P., Roll, J. P. and Forget R. (2009). Postural changes after sustained neck muscle contraction in persons with a lower leg amputation. *Journal of Electromyography and Kinesiology*. 19(4): e214-e222.
- Elfering, A., Dubi, M. and Semmer, N. K. (2010). Participation during Major Technological Change and Low Back Pain. *Industrial Health*. 48: 370-375.

- Entzel, P., Albers, J. and Welch, L. (2007). Best practices for preventing musculoskeletal disorders in masonry: Stakeholder perspectives. *Applied Ergonomics*. 38(5): 557-566.
- Faber, G. S., Kingma, I., Bakker, A.J. and Van Dieën, J. H. (2009). Low-back loading in lifting two loads beside the body compared to lifting one load in front of the body. *Journal of Biomechanics* 42(1): 35-41.
- Fong, B. F., Savelsbergh, G. J., Leijssen, M. R., and de Vries J. I. (2009). The influence of prenatal breech presentation on neonatal leg posture. *Early Human Development* 85(3): 201-206.
- Frievalds, A., Kong, Y., You, H. and Park, S. (2000). A comprehensive risk assessment model for work-related musculoskeletal disorders of the upper extremities. Ergonomics for the New Millennium. *Proceedings of the XIVth Triennial Congress of the International Ergonomics Association and the 44th Annual Meeting of the Human Factors and Ergonomics Society, San Diego CA, USA*. 29 July. Human Factors and Ergonomics Society, Santa Monica, CA, USA, Volume 5.
- Goldsheyder, D., Weiner, S.S., Nordin, M. and Hiebert, R. (2004). Musculoskeletal symptom survey among cement and concrete workers. *Work*. 23(2),111-21.
- Gorelick, M., Brown, J. M. and Groeller H. (2003). Short-duration fatigue alters neuromuscular coordination of trunk musculature: implications for injury. *Applied Ergonomics*. 34(4), 317-325.
- Gregory, D. E. and J. P. Callaghan (2008). Prolonged standing as a precursor for the development of low back discomfort: An investigation of possible mechanisms. *Gait & Posture*. 28(1), 86-92.
- Hales, T. R. and Bernard, B. P. (1996). Epidemiology of work-related musculoskeletal disorders. *Orthop. Clin. North Am.*(27): 679-709.
- Hall, C. (1997). External pressure at the hand during object handling and work with tools. *International Journal of Industrial Ergonomics* 20(3): 191-206.
- Halperin, K. M. and M. McCann (2004). An evaluation of scaffold safety at construction sites. *Journal of Safety Research* 35(2): 141-150.
- Hansson, G. Å., Balogh, I., Ohlsson, K., Rylander. L. and Skerfving, S. (1996). Goniometer measurement and computer analysis of wrist angles and movements applied to occupational repetitive work. *Journal of Electromyography and Kinesiology* 6(1): 23-35.

- Hasson, G-A., Asterland, P., Holmer, N-G. and Skerfving, S. (2001). Validity, reliability and applications of an inclinometer based on accelerometers. In: Hagberg M, Knave B, Lillienberg L, Westberg H, eds. *X2001—Exposure Assessment in Epidemiology and Practice*. Stockholm, Sweden: National Institute for Working Life S-112 79, 405–407.
- Hess, J.A., Hecker, S., Weinstein, M. And Lunger, M. (2004). A participatory intervention to reduce the risk of low-back injury in concrete laborers. *Applied Ergonomics*. 35(5), 427-41.
- Hignett, S. and L. McAtamney (2000). Rapid Entire Body Assessment (REBA). *Applied Ergonomics*. 31(2), 201-205.
- Holmstrom, E., Moritz, U. and Engholm, G. (1995). Musculoskeletal disorders in construction workers. *Occupational Medicine-State of the Art Reviews*. 10, 295-312.
- IOSH, 1996. *Evaluating the Cumulative Trauma Disorders Problem in the Semiconductors Industry*. Taiwan, ROC: Institute of Occupational Safety and Health, IOSH 85-H326.
- Jäger, M., Luttmann, A. and Wolfgang Laurig (1991). Lumbar load during one-handed bricklaying. *International Journal of Industrial Ergonomics*. 8(3): 261-277.
- Jorgensen, K., Jensen, B.R. and Kato, M. (1991). Fatigue development in the lumbar paravertebral muscles of bricklayers during the working day. *International Journal of Industrial Ergonomics*. 8(3): 237-245.
- Kadefors, R. and Forsman, M. (2000). Ergonomic evaluation of complex work: a participative approach employing video computer interaction, exemplified in a study of order picking. *Int J Ind Ergon*. 25: 435–445.
- Karhu, O., Kansil, P. and Kuorinka, I. (1977). Correcting working postures in industry: A practical method for analysis. *Applied Ergonomics* 8(4): 199-201.
- Karnezis, I. A. (2005). Correlation between wrist loads and the distal radius volar tilt angle. *Clinical Biomechanics*. 20(3): 270-276.
- Kawano, T. (2005). Development of Measuring Device for Lower Leg Swelling Using a Strain Gauge. JSME. *International Journal Series C*. 4, 592-597.
- Kee, D. and Karwowski, W. (2001). LUBA: an assessment technique for postural loading on the upper body based on joint motion discomfort and maximum holding time. *Applied Ergonomics* 32: 357-366.

- Ketola, R., Toivonen, R. and Viikari-Juntura, E. (2001). Interobserver repeatability and validity of an observation method to assess physical loads imposed on the upper extremities. *Ergonomics*. 44(119-131).
- Keyserling, W. M., Brouwer, M. and Silverstein, B.A. (1992). A checklist for evaluating ergonomic risk factors resulting from awkward postures of the legs, trunk and neck. *International Journal of Industrial Ergonomics*. 9(4): 283-301.
- Keyserling, W. M., Brouwer, M., Silverstein, B. A. (1993). The effectiveness of a joint labor-management program in controlling awkward postures of the trunk, neck, and shoulders: Results of a field study. *International Journal of Industrial Ergonomics*. 11(1): 51-65.
- Khan, A. A., L. O'Sullivan, O'Sullivan, L., Gallwey T. J. (2010). Effect on discomfort of frequency of wrist exertions combined with wrist articulations and forearm rotation. *International Journal of Industrial Ergonomics*. 40(5): 492-503.
- Kilbom, A. (1994a). Assessment of physical exposure in relation to workrelated musculoskeletal disorders—what information can be obtained from systematic observations? *Scand. J. Work Environ. Health*. 20(special issues): 30-45.
- Kilbom, A. (1994b). Repetitive work of the upper extremity: part II—the scientific basis (knowledge base) for the guide. *International Journal of Industrial Ergonomics*. 14: 59–86.
- Kuorinka, I. (1998). The influence of industrial trends on work-related musculoskeletal disorders (WMSDs). *International Journal of Industrial Ergonomics*. 21(1): 5-9.
- Khan, A. A., Sullivan, L. and Gallwey, T. J. (2010). Effect on discomfort of frequency of wrist exertions combined with wrist articulations and forearm rotation. *International Journal of Industrial Ergonomics*. 40(5): 492-503.
- Kuorinka, I. (1998). The influence of industrial trends on work-related musculoskeletal disorders (WMSDs). *International Journal of Industrial Ergonomics*. 21(1): 5-9.
- Krejcie, R. and Morgan, D. (1970). Determining sample size for research activities. *Educational and Psychological Measurement*. 30:607-610.
- Kroemer and Grandjean (1997). *Fitting the Task to the Human*. (5th Edition) Philadelphia: Taylor & Francis.

- Latko, W. A., Armstrong, T. J., Franzblau, A., Ulin, S. S., Werner, R. A. and Albers, J. W. (1999). Cross-sectional study of the relationship between repetitive work and the prevalence of upper limb musculoskeletal disorders. *Am. J. Ind. Med.* 36: 248–259.
- Li, G. and Buckle, P. (1999a). Current techniques for assessing physical exposure to work-related musculoskeletal risks, with emphasis on posture-based methods. *Ergonomics*. 42, 674-695.
- Li, G. and Buckle, P. (1999b). *Evaluating Change in Exposure to Risk for Musculoskeletal Disorders—A Practical Tool*. University of Surrey, Guildford: Health and Safety Executive.
- Lin, V. (1991). *Health, Women's Work, and Industrialization: Semiconductor Workers in Singapore and Malaysia* (174). New York & London: Garland Publishing.
- Lipscomba, H. J., Glaznerb, J. E., Bondy, J., Guarinic, K. and Lezotteb, D. (2006). Injuries from slips and trips in construction. *Applied Ergonomics*. 37(3): 267-274.
- Luttmann, A, Jäger, M. and Laurig, W. (1991). Task analysis and electromyography for bricklaying at different wall heights. *International Journal of Industrial Ergonomics* .8(3): 247-260.
- Maiti, R. (2008). Workload assessment in building construction related activities in India. *Applied Ergonomics* 39(6): 754-765.
- Malchaire, J. B., Roquelaure, Y., Cock, N. , Piette, A., Vergracht, S. and Chiron, H. (2001). Musculoskeletal complaints, functional capacity, personality and psychosocial factors. *Int .Arch .Occup .Environ. Health*. (74): 549-557.
- Marras, W., Fathallah, F., Miller, R., Davis, S. and Mirka, G. (1992). Accuracy of a three-dimensional lumbar motion monitor for recording dynamic trunk motion characteristics. *Int J Ind Ergon*. 9:75–87.
- McAtamney, L. and Corlett, E. N. (1993). RULA: a survey method for the investigation of work-related upper limb disorders. *Applied Ergonomics*. 24(2): 91-99.
- McDowell, T. W., Wiker, S. F., Donga, R. G. , Welcomea, D.E. and Schoppera A.W. (2006). Evaluation of psychometric estimates of vibratory hand-tool grip and push forces. *International Journal of Industrial Ergonomics*. 36(2): 119-128.

- Merletti, R. and Parker, P. (1999). Electromyography. In: *Wiley Encyclopaedia of Electrical and Electronics Engineering*, Vol. 6 : 523–540.
- Mogk, J. P. M. and Keir, P. J. (2008). Wrist and carpal tunnel size and shape measurements: Effects of posture. *Clinical Biomechanics*. 23(9): 1112-1120.
- Mork, P. J. and R. H. Westgaard (2009). Back posture and low back muscle activity in female computer workers: A field study. *Clinical Biomechanics*. 24(2): 169-175.
- Necking, L. E., Lundborg, G., Lundström, R., Thornell, L. E. and Fridén, J. (2004). Hand muscle pathology after long-term vibration exposure. *The Journal of Hand Surgery: Journal of the British Society for Surgery of the Hand*. 29(5): 431-437.
- Neumann, W. P., Wells, R. P., Norman, R.W., Frank, J., Shannon, H. and Kerr, M.S. (2001a). Trunk posture : reliability, accuracy, and risk estimates for low back pain from a video based assessment method. *International Journal of Industrial Ergonomics*. 28(6): 355-365.
- Neumann, W. P., Wells, R. P., Norman, R.W., Frank, J., Shannon, H. and Kerr, M.S. (2001b). A posture and load sampling approach to determining low-back pain risk in occupational settings. *International Journal of Industrial Ergonomics*. 27(2): 65-77.
- Nimbarte, A. d., Aghazadeh, F., Ikuma, L.H. and Harvey, C.M. (2010). Neck Disorders among Construction Workers: Understanding the Physical Loads on the Cervical Spine during Static Lifting Tasks. *Industrial Health*. 48: 145-153.
- Noy, Y. I., Lemoine, T. L., Klachan, C. and Burns, P.C. (2004). Task interruptability and duration as measures of visual distraction. *Applied Ergonomics*. 35(3): 207-213.
- Occupational Safety and Health Administration (OSHA) (2000). *Ergonomics program standard*. Washington, DC: Occupational Safety and Health Administration (OSHA).
- Pocockay, D., McCurdy, S. A., Samuels, S. J., Hammond, K. and Schenker, M. B. (1995). A cross-sectional study of musculoskeletal symptoms and risk factors in semiconductor workers. *American Journal of Industrial Medicine*. 28, 861-871.
- Pope, D., Silman, A., Cherry, N., Pritchard, C. and MacFarlane G. (1998). Validity of a self completed questionnaire measuring the physical demands of work. *Scand J Work Environ Health*. 24:376–385.

- Punnett, L. and Wegman, D. H. (2004). Work-related musculoskeletal disorders: the epidemiologic evidence and the debate. *Journal of Electromyography and Kinesiology*. 14(1): 13-23.
- Radwin, R. and Lin, M. (1993). An analytical method for characterizing repetitive motion and postural stress using spectral analysis. *Ergonomics*. 36:379–389.
- Roscoe, J. T. (1975). *Fundamental research statistics for the behavioral sciences* (2nd ed.). New York: Holt, Rineheart and Winston.
- Rossignol, A.M., Morse, E.P., Summers, V.M. and Pagnotto, L.D. (1987). Video display terminal use and reported health symptoms among Massachusetts clerical workers. *Journal of Occupational Medicine*. 29(2), 112–118.
- Rudy, T. E., Boston, J. R., Lieber, S. J., Kubinski, J. A. and Stacey, B. R. (2003). Body motion during repetitive isodynamic lifting: a comparative study of normal subjects and low-back pain patients. *Pain*. 105(1-2): 319-326.
- Schuldt, K., Ekholm, J., Harms-Ringdahl, K., Aborelius, U. and Nemeth, G. (1987). Influence of sitting postures on neck and shoulder emg during arm-hand work movements. *Clin Biomech*. 2:126–139.
- Shinya, M., Yamada, Y. and Oda S. (2009). Weight distribution influences the time required to lift the leg even under normal standing condition. *Gait & Posture*. 29(4): 623-627.
- Sillanpaa, J., Nyberg, M., Laippala, P. (2003). A new table for work with a microscope, a solution to ergonomic problems. *Applied Ergonomics*. 34 (6), 621–628.
- Spielholz, P., Silverstein, B., Morgan, M., Checkoway, H. and Kaufman, J. (2001). Comparison of self-report, video observation and direct measurement methods for upper extremity musculoskeletal disorder. *Ergonomics*. 44:588–613.
- Snook, S. H., Ciriello, V. M. and Webster, B. S. (1999). Maximum acceptable forces for repetitive wrist extension with a pinch grip. *International Journal of Industrial Ergonomics*. 24(6): 579-590.
- Straker, L. M., Sullivan, P. B., Smith, A. J. and Perry, M. C. (2009). Relationships between prolonged neck/shoulder pain and sitting spinal posture in male and female adolescents. *Manual Therapy*. 14(3): 321-329.
- Sturmer, T., Luessenhoop, S., Neth, A., Soyka, M., Karmaus, W., Toussaint, R., Liebs, T.R. and Rehder, U. (1997). Construction work and low back disorder.

- Preliminary findings of the Hamburg Construction Worker Study. *Spine (Phila Pa 1976.)* 22:2558-2563.
- Sullivan, P. B., Mitchell, T., Bulich, P., Waller, R. and Holte, J. (2006). The relationship between posture and back muscle endurance in industrial workers with flexion-related low back pain. *Manual Therapy*. 11(4): 264-271.
- Sullivan, M. J., Thibault, P., Andrikonyte, J., Butler, H., Catchlove, R. and Larivière C. (2009). Psychological influences on repetition-induced summation of activity-related pain in patients with chronic low back pain. *Pain*. 141(1-2): 70-78.
- Szeto, G. P., Straker, L. and Raine, S. (2002). A field comparison of neck and shoulder postures in symptomatic and asymptomatic office workers. *Applied Ergonomics*. 33(1): 75-84.
- Szeto, G.P., Straker, L.M. and O'Sullivan, P. B. (2009). Neck-shoulder muscle activity in general and task-specific resting postures of symptomatic computer users with chronic neck pain. *Manual Therapy*. 14(3): 338-345.
- Takala, E. P., Pehkonen, I., Forsman, M., Hansson, G. A. and Mathiassen, S. E. (2010). Systematic evaluation of observational methods assessing biomechanical exposures at work. *Scand J Work Environ Health*. 36(1): 3-24.
- Talis, V. L., Grishin, A. A., Solopova, I. A., Oskanyan, T. L., Belenky, V. E. and Ivanenko, Y. P. (2008). Asymmetric leg loading during sit-to-stand, walking and quiet standing in patients after unilateral total hip replacement surgery. *Clinical Biomechanics*. 23(4): 424-433.
- Tan, G. L. E. (1994). Ergonomic task analysis in electronics industries: some case studies. In: Ergonomics for Productivity and Safe Work. *Proceedings of the 4th South-East Asia Ergonomics Society and Safety and Health at Work Promotion Association International Conference*. Bangkok, 274–96.
- Thigpen, C. A., Padua, D. A., Michener, L. A., Guskiewicz, K., Giuliani, C., Keener, J.D. and Stergiou, N. (2010). Head and shoulder posture affect scapular mechanics and muscle activity in overhead tasks. *Journal of Electromyography and Kinesiology*. 20(4): 701-709.
- Van der Beek, A. J. and Frings-Dresen, M. H. W. (1998). Assessment of mechanical exposure in ergonomic epidemiology. *Occupational Environmental Medicine*. 55: 291-299.

- Veiersted, K. B., Gould, K. S., Osterås, N. and Hansson, G.A. (2008). Effect of an intervention addressing working technique on the biomechanical load of the neck and shoulders among hairdressers. *Applied Ergonomics*. 39(2): 183-190.
- Vi, P., Marks, N. and McCusker, M. (2000). Re-designing concrete cellular blocks to reduce the risk of low-back injury. *In: Proceedings of the IEA 2000/HFES 2000 Congress*. Santa Monica, California: Volume 5, 695-698.
- Viikari, E., Rauas, S., Martikainen, R., Kumosa, E., Riihimäki, H. and Saarenmaa K. (1996). Validity of self-reported physical work load in epidemiological studies on musculoskeletal disorders. *Scand J Work Environ Health*. 22:251–259.
- Village, J., Trask, C., Luong, N., Chow, Y., Johnson, P., Koehoorn, M. and Teschke, K. (2009). Development and evaluation of an observational Back-Exposure Sampling Tool (Back-EST) for work-related back injury risk factors. *Applied Ergonomics*. 40: 538-544.
- Visser, B., de Korte, E., van der Kraan, I. and Kuijer, P. (2000). The effect of arm and wrist supports on the load of the upper extremity during VDU work. *Clinical Biomechanics*. 15(Supplement 1): S34-S38.
- Wald, P.H. and Jones, J.R. (1987). Semiconductor manufacturing: an introduction to processes and hazards. *American Journal of Industrial Medicine*. 11(2), 203–221.
- Wang, M. J. J., Chung, H. C., and Wu, H. C. (2004). Evaluating the 300mm wafer handling task in semiconductor industry. *International Journal of Industrial Ergonomics*. 34, 459-466.
- Wai, E. K., Roffey, D.M., Bishop, P., Kwon, B.K. and Dagenais, S. (2009). Causal assessment of occupational bending or twisting and low back pain: results of a systematic review. *The Spine Journal*. 10(1): 76-88.
- Welcomme, D., Rakhejab, S., Donga, R., Wua, J.Z. and Schoppera, A.W. (2004). An investigation on the relationship between grip, push and contact forces applied to a tool handle. *International Journal of Industrial Ergonomics*. 34(6): 507-518.
- Wells, R., Norman, R., Neuman, P., Andrews, D., Frank, J. and Shannon, H. (1997). Assessment of physical work load in epidemiologic studies: Common measurement metrics for exposure assessment. *Ergonomics*. 40:51–61.
- Weon, J. H., Oh, J. S., Cynn, H.S., Kim, Y. W., Kwon, O. Y. and Yi, C. H. (2010). Influence of forward head posture on scapular upward rotators during isometric

- shoulder flexion. *Journal of Bodywork and Movement Therapies*. 14(4): 367-374.
- Winkel, J. and Westgaard, R. (1992). Occupational and individual risk factors for shoulder–neck complaints: part II—the scientific basis (literature review) for the guide. *Int. J. Ind. Ergonomic*. 10: 85-104.
- Winkel, J. and Mathiassen, S. E. (1994). Assessment of physical work load in epidemiologic studies: concepts, issues and operational considerations. *Ergonomics*. 37: 979-988.
- Woon, K.S., Rahmana, M., Neoa, K.S. and Liub, K. (2008). The effect of tool edge radius on the contact phenomenon of tool-based micromachining. *International Journal of Machine Tools and Manufacture*. 48(12-13): 1395-1407.
- Wong, T. K. T. and Lee, R. Y. W. (2004). Effects of low back pain on the relationship between the movements of the lumbar spine and hip. *Human Movement Science*. 23(1): 21-34.
- Yu, C.Y., Chen, Y.C., Yen, W.Y., and Lin, Y.H. (2003). A preliminary investigation of the causes of musculoskeletal fatigue in semiconductor workers. *Journal of Occupational Safety and health*. 1,1-18.

